

KB20A335

CAPACITIVE SENSORS • NORM SWITCHING DISTANCE

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.

MECHANICAL DATA

Cable length	2 m
Housing design	Cylinder plain
Mechanical mounting condition for sensor	Flush
Pressure-proof	No
Sensor diameter	20 mm
Sensor height	40 mm

ELECTRICAL DATA

Cascadable	No
Suitable for safety functions	No
Supply voltage	8 V ... 8 V
Switching distance	8 mm
Type of electrical connection	Cable
Voltage type	DC
With monitoring function of downstream devices	No

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

