

PT380523

LASER SENSORS • DIFFUSE REFLECTION SENSORS WITH BACKGROUND SUPPRESSION

Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.



MECHANICAL DATA

Ambient temperature (MAX)	40 °C
Ambient temperature (MIN)	-10 °C
Degree of protection (IP)	IP67
Housing design	Cuboid
Housing material	Metal
Material of optical surface	Glass
Reflector included in the scope of delivery	No
Sensor height	48 mm
Sensor length	38 mm
Sensor width	15 mm
Storage temperature	40 °C
Storage temperature	-10 °C

ELECTRICAL DATA

Adjustment range (MAX)	400 mm
Adjustment range (MIN)	50 mm
Analogue output 0 mA ... 20 mA	No
Analogue output 0 V ... 10 V	No
Analogue output -10 V ... +10 V	No
Analogue output 4 mA ... 20 mA	No
Laser power	1 mW
Max. output current	100 mA
Max. switching distance	400 mm
No-load current	35 mA
Number of pins	5
Number of switching outputs	2
Operating voltage (MAX)	30 V


ELECTRICAL DATA

Operating voltage (MIN)	18 V
Rated switching distance	400 mm
Readiness delay	100 ms
Reverse polarity protection	Yes
Sensing range (MAX)	400 mm
Sensing range (MIN)	5 mm
Setting procedure	Manual adjustment
Short-circuit-proof	Yes
Switching frequency	2000 Hz
Type of electrical connection	Connector M12
Type of switching function	Normally open contact (NO)
Type of switching output	PNP/NPN
Voltage type	DC
With LED display	Yes
With LED display (functional reserve)	Yes
With LED display (operation)	Yes
With LED display (signal)	Yes
With other analog output	No

OPTICAL DATA

Background suppression	Yes
Laser class	2
Laser focus distance	350 mm
Light beam form	Point
Light source	Laser diode, red light
Light spot	0.79 mm ²
Triangulation	Background suppression
Wavelength of the sensor	670 nm

CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 2 = NPN NO, 3 = L-, 4 = PNP NO

DIMENSIONAL DRAWING

INSTALLATION

DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.