

## KN18C379

### CAPACITIVE SENSORS • ENLARGED AMBIENT TEMPERATURE

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.

#### MECHANICAL DATA

Active area material of sensor	PTFE
Ambient temperature	-25 °C ... 70 °C
Cable length	5 m
Degree of protection (IP)	IP67
Housing design	Cylinder, screw-thread
Housing material	PTFE
Material of cable sheath	PVC
Mechanical mounting condition for sensor	Non-flush
Number of wires	4
Pressure-proof	No
Sensor length	70 mm
Teflon housing	Yes
Thread pitch	1 mm
Thread size, metric	18
Wire cross section	0.34 mm <sup>2</sup>

#### ELECTRICAL DATA

Cascadable	No
Max. output current	250 mA
No-load current	15 mA
Number of switching outputs	2
Residual ripple	10 %
Suitable for safety functions	No
Supply voltage	10 V ... 35 V
Switching distance	15 mm
Switching distance	0.5 mm ... 15 mm
Switching frequency	50 Hz
Type of electrical connection	Cable
Type of switching output	PNP
Voltage drop	2 V
Voltage type	DC

**ELECTRICAL DATA**

With LED display

Yes

With monitoring function of downstream devices

No

**DIMENSIONAL DRAWING****INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL****SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!