

VKSI0312

CONNECTION TECHNOLOGY • CABLE SOCKETS /CONNECTORS TWO-SIDED PRE-ASSEMBLED

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



MECHANICAL DATA

Cable length	3 m
Cable sheath color	Black
Material of cable sheath	PUR (Polyurethane)
Number of wires	4
Positioning of cable feed, field side	Angled
Positioning of cable feed, housing side	Angled


ELECTRICAL DATA

Number of pins	4
Number of pins, housing side	4
Shielded	No
Type of cable	Multi-core
Type of electrical connection, field side	M9
Type of electrical connection, housing side	M9
Type of plug-in contact, field side	Male (plug)
Type of plug-in contact, housing side	Male (plug)


OTHER DATA

Flame resistant	No
Halogen-free	No
IR-networked	No
Suitable for trailing chain and torsion resistant	Yes
Welding area	Yes

CONNECTION



DIMENSIONAL DRAWING



INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.