

KB320000**CAPACITIVE SENSORS • SENSORS WITH ANALOG OUTPUT**

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.

MECHANICAL DATA

Active area material of sensor	PTFE
Ambient temperature (MAX)	60 °C
Cable length	2 m
Degree of protection (IP)	IP67
Housing design	Cylinder, screw-thread
Housing material	Brass
Material of cable sheath	PUR (Polyurethane)
Mechanical mounting condition for sensor	Flush
Number of wires	3
Pressure-proof	No
Sensor length	70 mm
Thread pitch	1.5 mm
Thread size, metric	32
Wire cross section	0.75 mm ²

ELECTRICAL DATA

Cascadable	No
Distance measuring sensors	Yes
No-load current	40 mA
Residual ripple	5 %
Reverse polarity protection	Yes
Setting procedure	Manual adjustment
Short-circuit-proof	Yes
Suitable for safety functions	No
Supply voltage	15 V ... 30 V
Switching distance	30 mm
Switching distance (MAX)	30 mm
Type of analog output	4 mA ... 20 mA
Type of electrical connection	Cable
Voltage type	DC
With LED display	Yes

ELECTRICAL DATA

With monitoring function of downstream devices

No

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!