

## IN990013

### INDUCTIVE SENSORS • NORM SWITCHING DISTANCE

Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts /bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.



#### MECHANICAL DATA

Active area material of sensor	PBT
Ambient temperature (MAX)	80 °C
Ambient temperature (MIN)	-25 °C
Degree of protection (IP)	IP65
Housing design	Cylinder plain
Housing material	PBT
Mechanical mounting condition for sensor	Non-flush
Pressure-proof	No
Sensor diameter	20 mm
Sensor length	92 mm

#### ELECTRICAL DATA

Cascadable	No
Max. output current	350 mA
Suitable for safety functions	No
Supply voltage (MAX)	250 V
Supply voltage (MIN)	20 V
Switching distance	10 mm
Type of electrical connection	Clamp
Type of switching function	Programmable/configurable
Type of switching output	PNP
Voltage type	AC/DC
With monitoring function of downstream devices	No

#### DIMENSIONAL DRAWING

#### INSTALLATION

#### DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.