




Product information BAT867-R - BAT867-R Europe

Industrial Ethernet:Industrial Wireless LAN:Devices:BAT867-R:BAT867-R	
http://dev-catalog.beldensolutions.com/link/57078-24455-49859-24497-488175-500755/en/BAT867-REUW99AU999AT199L999ZH09.14.5700/uistate	
Name	BAT867-R
	
	Rugged wireless LAN access point and/or client with IEEE 802.11ac for use in industrial environments.
Delivery informations	
Availability	available
Product description	
Description	Rugged wireless LAN access point and/or client with IEEE 802.11ac for use in industrial environments.
Port type and quantity	Interface1: - Ethernet port 1 : RJ 45 (10/100/1000BASE-TX data rates)
Radio Standard	IEEE 802.11a/b/g/n/ac WLAN interface as per IEEE 802.11ac, up to 867 Mbit/s gross bandwidth.
Additional radio features	2x2 MIMO
Type	BAT867-R Europe
Order No.	942183001
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin
Radio technology	
Antenna connector	2 x RSMA
Range	Depending on antenna used, frequency range and data rate
Frequency band	Supporting 2.4 GHz and 5 GHz: 2412 to 2472 MHz and 5180 to 5825 MHz
Modulation	OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
Encryption	IEEE 802.11i / WPA2 with passphrase or 802.1x and hardware-accelerated AES, closed network, WEP64, WEP128, WEP152, user authentication, 802.1x / EAP, LEPS, WPA1/TKIP. Please refer to the HiLCOS data sheet for further information.
Power requirements	
Operating voltage	Voltage Range 1: 24 VDC (19.2-32 VDC)
Power consumption	Maximum power consumption : 9 W
Ambient conditions	
Operating temperature	-10 °C ... 60 °C
Note	Temperature of the surrounding air.
Storage/transport temperature	-40 °C ... 70 °C
Relative humidity (non-condensing)	10 % ... 95 %
MTBF (Telcordia)	286.8 years; Telcordia SR-332; Gb 25°C
Protective paint on PCB	No
Software	
Software features	High performance operating system for the Hirschmann BAT products. Supports all WLAN functions, routing, firewall, VLAN, and redundancy. IPv6 in preparation. All BAT867-R devices operate as either standalone access points or as managed access points in combination with a BAT WLC Controller. Please refer to the HiLCOS data sheet for further information.
Mechanical construction	
Dimensions (W x H x D)	50 mm x 147.5 mm x 122.5 mm
Mounting	DIN Rail
Protection class	IP40
Approvals	
Basis Standard	CE, EN 61131
Safety of information technology equipment	EN 60950-1
Radio	RED - EN 300 328 (2.4 GHz) EN 301 893 (5 GHz) EN 302 502 (5.8 GHz) , EN 301 489-1, EN 301 489-17, EN 61000-6-2
Railway norm	EN50121-4
Scope of delivery and accessories	
Scope of delivery	Device, Quick installation guide; 1 x premounted 2-pin terminal block for the supply voltage; 2 x Omnidirectional dual-band antennas for initial operation; 1 x 50-Ω terminator for equipping free antenna connections



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Industrial Wireless LAN:Devices:BAT867-R:BAT867-R

<http://dev-catalog.beldensolutions.com/link/57078-24455-49859-24497-488175-500755/en/BAT867-REUW99AU999AT199L999ZH09.14.5700/ui:state>

Accessories to order separately

External antennas; External surge protection; Cables 2m, 5m, 15m

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.