

**C1050101****COUNTERS • PULSE COUNTERS**

In industrial applications, counting, adding / subtracting of pulses, measuring paths or detecting times are common task areas. However, the use of a PLC is not worthwhile evaluating one or two sensors only. In this case, the multi-function encounters of ipf electronic are a good alternative. Various evaluation variants, amongst others frequency meters, sum counters, time relays, tachometers or wear / maintenance counters enable the use in a variety of applications. The batch counter or total sums function also make more complex tasks possible. The integrated front keypad can conveniently be used to program a pre-selection value or the signal evaluation mode for the operation of a linear measurement system or a rotary encoder.

**MECHANICAL DATA**

Ambient temperature (MAX)	45 °C
Degree of protection (IP)	IP65
Height	48 mm
Housing material	Noryl UL94
Installation depth	131.5 mm
Length	141 mm
Storage temperature	70 °C
Suitable for serial installation	No
Width	96 mm

**ELECTRICAL DATA**

1. output voltage at DC	5 V ... 30 V
2. output voltage at DC	5 V ... 30 V
3. output voltage at DC	5 V ... 30 V
4. output voltage at DC	30 V
4. output voltage at DC	5 V
Counting frequency	1000 kHz
Display	LED
Display range	9999999
Display range	-9999999
Input voltage frequency	1000000 Hz
Max. output current	0.35 mA
Max. output current 1	0.35 A
Max. output current 2	0.35 A
Max. output current 3	0.35 A
Max. output current 4	0.35 A
Number of decades	8
Number of pins	8
Number of switching outputs	4
Operating voltage	24 V ... 24 V
Primary voltage	24 V

**ELECTRICAL DATA**

Pulse counter	Yes
Rated control supply voltage Us at AC 50HZ	24 V ... 24 V
Rated control supply voltage Us at DC	17 V ... 40 V
Response time	1 ms
Type of 2nd switching function	Normally open contact (NO)
Type of 2nd switching output	PNP
Type of 3rd switching function	Normally open contact (NO)
Type of 3rd switching output	PNP
Type of 4th switching function	Normally open contact (NO)
Type of 4th switching output	PNP
Type of electrical connection	Screw connection
Type of switching function	Normally open contact (NO)
Type of switching output	PNP
Voltage type	AC/DC
With communication interface, RS-232	Yes

**OTHER DATA**

Number of characters	8
----------------------	---

**DIMENSIONAL DRAWING**

**INSTALLATION**



Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL**



**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!