

## KN834100

### CAPACITIVE SENSORS • NORM SWITCHING DISTANCE

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.



#### MECHANICAL DATA

Active area material of sensor	PBT
Ambient temperature	-25 °C ... 70 °C
Cable length	2 m
Degree of protection (IP)	IP67
Housing design	Cylinder plain
Housing material	PBT
Material of cable sheath	PVC
Mechanical mounting condition for sensor	Non-flush
Number of wires	2
Pressure-proof	No
Sensor diameter	100 mm
Sensor length	40 mm

#### ELECTRICAL DATA

Cascadable	No
Correction factor (glass)	0.6
Correction factor (oil)	0.5
Correction factor (PVC)	0.5
Correction factor (wood)	0.6
Hysteresis	15 %
Max. output current	400 mA
Min. output current	5 mA
No-load current	2.5 mA
Rated control supply voltage $U_s$ at AC 50HZ	20 V ... 250 V
Suitable for safety functions	No
Supply voltage	20 V ... 250 V
Switching distance	70 mm
Switching distance	1 mm ... 120 mm
Switching frequency	10 Hz
Type of electrical connection	Cable
Type of switching function	Normally open contact


**ELECTRICAL DATA**

Type of switching output	Two-wire
Voltage drop	10 V
Voltage type	AC
With LED display	Yes
With monitoring function of downstream devices	No

**OTHER DATA**

Level detection	Yes
-----------------	-----

**DIMENSIONAL DRAWING**



**INSTALLATION**



Mounting / Installation may only be carried out by a qualified electrician!

**DISPOSAL**



**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!