

CZ990804

COUNTERS • TIME DELAY COUNTERS

Elapsed-time counters are versatile. Various operating tasks can be solved by simple operating hour counters to the start- or stop-delay of switching signals up to the stopwatch in the millisecond range with adjustable switching threshold. In addition to the basic devices with largely fixed settings, multit talents can be set with parameters and functions via DIP-switches or membrane keyboard.



MECHANICAL DATA

Degree of protection (IP)	IP65
Height	48 mm
Housing material	Plastic
Installation depth	93 mm
Length	100 mm
Mounting method	Panel mounting
Storage temperature	70 °C
Storage temperature	-20 °C
Width	48 mm

ELECTRICAL DATA

Display	LED
Number of decades	2
Number of pins	5
Number of presets to be set	1
Number of switching outputs	1
Rated control supply voltage U_s at DC	24 V ... 24 V
Rated switching current	1 A
Type of electrical connection	Screw connection
Type of signal input A	Two-wire
Type of switching output	Relay contact
Voltage type	AC/DC

DIMENSIONAL DRAWING

INSTALLATION

DISPOSAL



Mounting / Installation may only be carried out by a qualified electrician!



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!