

**VK003076**

**CONNECTION TECHNOLOGY • CABLE SOCKETS FIELD-ATTACHABLE**

ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.



**MECHANICAL DATA**

Contact body material	CuZn
Contact coating material	Au
Degree of protection (IP)	IP67
Housing material	Brass
Number of wires	3
Perm. ambient temperature of cable, fixed cable (MAX)	85 °C
Perm. ambient temperature of cable, fixed cable (MIN)	-40 °C
Positioning of cable feed, housing side	Angled
Wire cross section	0.25 mm <sup>2</sup>


**ELECTRICAL DATA**

Number of pins	3
Rated current I <sub>n</sub>	4 A
Rated voltage	60 V
Suitable for self-assembly	Yes
Type of electrical connection, housing side	M8
Type of plug-in contact, housing side	Male (plug)
With LED display	No


**OTHER DATA**

Flame resistant	No
IR-networked	No

## CONNECTION



## DIMENSIONAL DRAWING



## INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

## DISPOSAL



## SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.