




## Product information M-XFP-ZR/LC

Industrial Ethernet: System Accessories: Transceiver: 10 Gigabit Ethernet XFP and SFP+ Transceiver: M-XFP-ZR/LC

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24535-24530-40332/en/conf/uistate>

Name	M-XFP-ZR/LC
	
	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
Order No.	943 921-001
Port type and quantity	1 x 10GBASE with LC Connector
Type	M-XFP-ZR/LC
<b>Network size - length of cable</b>	
Single mode fiber (SM) 9/125 µm	40 - 80 km, 1550 nm; 11-24 dB link budget, 0.25 dB/km, 19 ps/(nm*km)
<b>Service</b>	
Diagnostics	optical input- and output power, transceiver temperature
<b>Technical data</b>	
Operating voltage	power supply via media module
Operating temperature	0 °C to +50 °C
Relative humidity (non-condensing)	5% - 95%
Power consumption	3 W
<b>Approvals</b>	
Basis Standard	FCC, RCM
Safety of information technology equipment	cUL 60950-1
Transportation	EN50121-4

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.