



Product information RPS60/48V EEC

Industrial Ethernet: System Accessories: Power Supplies and Cables: Power Supplies: RPS60/48V EEC

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24545-503476-40457/en/conf/ui/state>

Name	RPS60/48V EEC
	
	48 V DC rail power supply unit
Delivery informations	
Availability	available
Product description	
Description	48 V DC rail power supply unit
Type	RPS60/48V EEC
Order No.	943 952-001
More Interfaces	
Voltage input	1 Federkraft-Klemmblock, 4-polig
Voltage output	1 Federkraft-Klemmblock, 4-polig
Power requirements	
Operating voltage	230 V
Input data	
Input voltage	100 to 240 V AC; 50-60Hz or; 85 to 264 V AC; 47-63Hz (DC 100 to 375V)
Current consumption	
Current consumption	Max. 0.7 A at 230 V; max. 1.3 A at 100V
Activation current	< 40 A at 264 V AC
Output data	
Output voltage	47-52 V DC (typ. 48 V); externally adjustable
Output current	
Output current	1,25 A static at 48 V nominal; 1,88 A (150% of nominal load) for max. 2,5 seconds
Service	
Diagnostics	LED (green)
Ambient conditions	
Operating temperature	-20 °C to +70 °C
Storage/transport temperature	-25 °C to +85 °C
Relative humidity (non-condensing)	max. 95 % without condensation
Mechanical construction	
Dimensions (W x H x D)	44,8 mm x 75 mm x 104,5 mm
Mounting	DIN Rail 35 mm
Weight	245 g
Protection class	IP 20
EMC interference immunity	
EN 50082-1	EN 61000-6-1
EN 50082-2	EN 61000-6-2
EMC emitted immunity	
EN 50081-1	61000-6-3, 61000-6-4, EN 55011, EN 55022 class A
EN 50081-2	harmonic input current, fulfills EN 61000-3-2
Approvals	
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Scope of delivery and accessories	
Scope of delivery	Rail power supply, ferrit with safety key, Description and operating manual

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.