



Product information RSPE Switches - RSPE32-2404407T99- SPPZ999HHSE2S06.0.

Industrial Ethernet:Power Rail Switches:RSPE Switches:with HiOS 6.0/7.0:RSPE Switches	
http://dev-catalog.beldensolutions.com/link/57078-24455-202442-411805-460710-460711/en/RSPE32-2404407T99-SPPZ999HHSE2S06.0/uistate	
Name	RSPE Switches
	
	Managed Fast/Gigabit Industrial Ethernet Switch, fanless design, Power over Ethernet (PoE+) support with up to 24 Ports and 120 Watt, 24x 10/100 Mbit/s Ethernet Ports, 4x 10/100/1000 Mbit/s Ethernet Ports, 4x FE/GE Combo ports, HiOS Layer 2 Standard
Delivery informations	
Availability	available
Product description	
Description	Managed Fast/Gigabit Industrial Ethernet Switch, fanless design, Power over Ethernet (PoE+) support with up to 24 Ports and 120 Watt, 24x 10/100 Mbit/s Ethernet Ports, 4x 10/100/1000 Mbit/s Ethernet Ports, 4x FE/GE Combo ports, HiOS Layer 2 Standard
Port type and quantity	4x GE plus 24 FE ports, Ports in total up to 28 Basic unit: 4x FE/GE Combo ports plus 8 FE TX ports expandable with two slots for media modules with 8 FE ports each, 16 fiber ports: 4 GE/FE basic unit plus 12 FE with media modules
Type	RSPE32-2404407T99-SPPZ999HHSE2S06.0.
Order No.	RSPE32-2404407T99-SPPZ999HHSE2S06.0.
More Interfaces	
Power supply/signaling contact	2x plug-in terminal block 2-pins, 1x plug-in terminal block 2-pins
V.24 interface	1 x RJ11 socket
SD-card slot	to connect auto-configuration adapter ACA21/22 (USB) or ACA31 (SD-card)
Network size - length of cable	
Twisted pair (TP)	0 m ... 100 m
Multimode fiber (MM) 50/125 µm	see SFP modules
Multimode fiber (MM) 62.5/125 µm	see SFP modules
Single mode fiber (SM) 9/125 µm	see SFP modules
Single mode fiber (LH) 9/125 µm (long haul transceiver)	see SFP modules
Network size - cascading	
Line - / star topology	any
Ring structure, quantity switches	MRP, RSTP, HSR
Power requirements	
Operating voltage	2x 47 - 57 VDC (POE) or 53 - 57 VDC (POE+)
Power consumption	maximum 36W depending on fiber port count plus PoE
Software	
Management	Dual Software Image Support; TFTP; SFTP; SCP; LLDP (802.1AB); LLDP-MED; SSHv2; V.24; HTTP; HTTPS; Traps; SNMP v1/v2/v3; Telnet; DNS Client
Diagnostics	Management Address Conflict Detection; MAC Notification; Signal Contact; Device Status Indication; TCPDump; LEDs; Syslog; Persistent Logging on ACA; Email Notification; Port Monitoring with Auto-Disable; Link Flap Detection; Overload Detection; Duplex Mismatch Detection; Link Speed and Duplex Monitoring; RMON (1,2,3,9); Port Mirroring 1:1; Port Mirroring 8:1; Port Mirroring N:1; RSPAN; SFLOW; VLAN Mirroring; System Information; Self-Tests on Cold Start; Copper Cable Test; SFP Management; Configuration Check Dialog; Switch Dump; Snapshot Configuration Feature
Configuration	Automatic Configuration Undo (roll-back); Configuration Fingerprint; Text-based Configuration File (XML); BOOTP/DHCP Client with Auto-Configuration; DHCP Server: per Port; DHCP Server: Pools per VLAN; AutoConfiguration Adapter ACA31 (SD card); AutoConfiguration Adapter ACA21/22 (USB); HiDiscovery; DHCP Relay with Option 82; Command Line Interface (CLI); CLI Scripting; Full-featured MIB Support; Web-based Management; Context-sensitive Help
Security	MAC-based Port Security; Port-based Access Control with 802.1X; Guest/unauthenticated VLAN; Integrated Authentication Server (IAS); RADIUS VLAN Assignment; RADIUS Policy Assignment; Multi-Client Authentication per Port; MAC Authentication Bypass; DHCP Snooping; Dynamic ARP Inspection; Automatic Denial-of-Service Prevention; LDAP; Ingress MAC-based ACL; Ingress IPv4-based ACL; Time-based ACL; VLAN-based ACL; Ingress VLAN-based ACL; ACL Flow-based Limiting; Access to Management restricted by VLAN; Device Security Indication; Audit Trail; CLI Logging; HTTPS Certificate Management; Restricted Management Access; Appropriate Use Banner; Configurable Password Policy; Configurable Number of Login Attempts; SNMP Logging; Multiple Privilege Levels; Local User Management; Remote Authentication via RADIUS; User Account Locking
Redundancy functions	Link Aggregation with LACP; Link Backup; Media Redundancy Protocol (MRP) (IEC62439-2); RSTP 802.1D-2004 (IEC62439-1); RSTP Guards

Industrial Ethernet: Power Rail Switches: RSPE Switches: with HiOS 6.0/7.0: RSPE Switches
<http://dev-catalog.beldensolutions.com/link/57078-24455-202442-411805-460710-460711/en/RSPE32-2404407T99-SPP2999HHSE2S06.0/uistate>

Industrial Profiles	EtherNet/IP protocol, IEC61850 protocol (MMS Server, Switch Model), ModbusTCP, PROFINET IO Protocol
Time synchronisation	PTPv2 Transparent Clock two-step; PTPv2 Boundary Clock; Buffered Real Time Clock; SNTP Client; SNTP Server
Miscellaneous	Manual Cable Crossing; Port Power Down
Switching	Independent VLAN Learning; Fast Aging; Static Unicast/Multicast Address Entries; QoS / Port Prioritization (802.1D/p); TOS/DSCP Prioritization; Interface Trust Mode; CoS Queue Management; IP Ingress DiffServ Classification and Policing; Queue-Shaping / Max. Queue Bandwidth; Flow Control (802.3X); Egress Interface Shaping; Ingress Storm Protection; Jumbo Frames; VLAN (802.1Q); Protocol-based VLAN; VLAN Unaware Mode; Voice VLAN; MAC-based VLAN; IP subnet-based VLAN; IGMP Snooping/Querier per VLAN (v1/v2/v3); Unknown Multicast Filtering; Multiple VLAN Registration Protocol (MVRP); Multiple MAC Registration Protocol (MMRP); Multiple Registration Protocol (MRP); GARP VLAN Registration Protocol (GVRP); GMRP
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 70 °C
Relative humidity (non-condensing)	10 % ... 95 %
Mechanical construction	
Dimensions (W x H x D)	209 mm x 164 mm x 120 mm
Mounting	DIN Rail
Weight	2.2kg plus media modules
Protection class	IP20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 2 kV data line IEC61000-4-5: power line 5 kV (line/earth)
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EN 61000-4-16 mains frequency voltage	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Basis Standard	CE, FCC, RCM, EN61131-2
Safety of industrial control equipment	EN 60950-1
Scope of delivery and accessories	
Scope of delivery	Device, terminal block, operating manual

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

 E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.