


SL90A834

FLOW SENSORS • SENSORS FOR AIR

The function of the flow sensor is based on the calorimetric principle. The probe is heated up from the inside a few degrees Celsius in relation to the flow medium, in which it protrudes. When the medium flows, the heat generated in the probe is dissipated through the medium. The temperature within the sensor is measured and compared with the likewise measured medium temperature. From the obtained temperature difference the flow state of each medium can be derived. These sensors are applied in areas such as monitoring of cooling systems, ventilation systems, pump dry running by checking the presence of liquid or gas flows.



MECHANICAL DATA

Cable length	2 m
Degree of protection (IP) of evaluation electronics	IP68
Degree of protection (IP) of measuring head	IP68
Housing design	Cylinder, screw-thread
Housing material	Stainless steel 1.4305
Material of cable sheath	PVC
Medium temperature (MAX)	80 °C
Number of wires	4
Pressure resistance	30 bar
Sensing element material	Stainless steel 1.4305
Type of process connection	G1/2 inch
Wire cross section	0.25 mm ²

ELECTRICAL DATA

Adjustable responding value for flow for gases	0.5 m/s ... 30 m/s
Air conditioning / ventilation systems	Yes
IO-Link compatible	No
Measuring principle of flow	Calorimetric
Pressure resistance of measuring head	30 bar
Readiness delay	90 ms
Response time	30000 ms
Type of electrical connection	Cable

OTHER DATA

For pneumatic applications	Yes
Suitable for gases	Yes
Suitable for liquids	No

DIMENSIONAL DRAWING**INSTALLATION**

Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!