

**KB990391****CAPACITIVE SENSORS • NORM SWITCHING DISTANCE**

Capacitive proximity switches are contact-free sensors. They detect metallic and non-metallic objects, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material, its dimensions and the response sensitivity, which is set via a potentiometer. The vibration-resistant sensors can be approached laterally or frontally. Capacitive proximity switches are used for presence detection (e.g. sealing detection), positioning (e.g. PET bottles), counting (e.g. plastic caps), level detection (e.g. lubricant) or distance measurements (e.g. thickness measurement) of solid and liquid materials.

**MECHANICAL DATA**

Active area material of sensor	PTFE
Ambient temperature	-25 °C ... 70 °C
Cable length	2 m
Degree of protection (IP)	IP67
Mechanical mounting condition for sensor	Flush
Pressure-proof	No

**ELECTRICAL DATA**

Cascadable	No
Max. output current	400 mA
No-load current	15 mA
Residual ripple	10 %
Suitable for safety functions	No
Supply voltage	10 V ... 35 V
Switching distance	25 mm
Switching frequency	50 Hz
Type of electrical connection	Cable
Type of switching output	NPN
Voltage drop	2 V
Voltage type	DC
With monitoring function of downstream devices	No

**DIMENSIONAL DRAWING****INSTALLATION****DISPOSAL**



Mounting / Installation may only be carried out by a qualified electrician!



**SAFETY WARNINGS**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!