




Product information M-XFP-LR/LC EEC

Industrial Ethernet: System Accessories: Transceiver: 10 Gigabit Ethernet XFP and SFP+ Transceiver: M-XFP-LR/LC EEC

<http://dev-catalog.beldensolutions.com/link/57078-24455-24544-24535-24530-501011/en/conf/ui/state>

Name	M-XFP-LR/LC EEC
	
	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
Delivery informations	
Availability	available
Product description	
Description	XFP Fiberoptic 10Gigabit-Ethernet Transceiver
Order No.	942 055-001
Port type and quantity	1 x 10GBASE with LC Connector
Type	M-XFP-LR/LC EEC
Network size - length of cable	
Single mode fiber (SM) 9/125 µm	Typ 10 km, 1310 nm; 7.8 dB link budget, 0.4 dB/km, 3.5 ps/(nm*km)
Service	
Diagnostics	optical input- and output power, transceiver temperature
Technical data	
Operating voltage	power supply via media module
Operating temperature	-40 °C to +85 °C
Relative humidity (non-condensing)	5% - 95%
Power consumption	3 W
Approvals	
Basis Standard	FCC, RCM
Safety of information technology equipment	cUL 60950-1
Transportation	EN50121-4

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.