


## Product information

### Greyhound 1040 - Module - GMM32-MMMMTTTSZ9HHS999.9

Industrial Ethernet:Ruggedized Switches:GREYHOUND Gigabit Ethernet-Switch, media modules and power supplies:with HiOS 6.0/7.0:Greyhound 1040 - Module

<http://dev-catalog.beldensolutions.com/link/57078-24455-49846-433327-459805-459935/en/GMM32-MMMMTTTSZ9HHS999.9/uistate>

Name	Greyhound 1040 - Module
	
	GREYHOUND1042 Fast/Gigabit Ethernet media module; PoE/PoE+ support (PoE power supply required)
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Type	GMM32-MMMMTTTSZ9HHS999.9
Order No.	GMM32-MMMMTTTSZ9HHS999.9
Description	GREYHOUND1042 Fast/Gigabit Ethernet media module; PoE/PoE+ support (PoE power supply required)
Port type and quantity	4 ports Fast Ethernet and 4 ports FE/GE; all copper ports support PoE/PoE+; 2 x FE MM, SC; 2 x FE MM, SC; 2x FE/GE, RJ45; 2x FE/GE, RJ45
<b>Network size - length of cable</b>	
Twisted pair (TP)	0 m ... 100 m
Multimode fiber (MM) 50/125 µm	0 - 5000 m, 8 dB Link Budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm	0 - 4000 m, 11 dB Link Budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 500 MHz x km
<b>Power requirements</b>	
Operating voltage	via switch
Power consumption	5.5 - 10W (without PoE)
<b>Ambient conditions</b>	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 70 °C
Relative humidity (non-condensing)	5 % ... 95 %
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line, IEEE1613: power line 5 kV (line/earth)
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EN 61000-4-16 mains frequency voltage	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
<b>Approvals</b>	
Safety of industrial control equipment	EN61131, EN60950
<b>Scope of delivery and accessories</b>	
Scope of delivery	Device, operating manual

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.