


UT139073

ULTRASONIC SENSORS • DISTANCE MEASUREMENT

sensor ultrasonic, diffuse-reflection sensor, 84x12x12mm, Sn: 40-400, 18-30V DC, 0-10V/4-20mA, IO-Link, Connector M8 4pin, IP67, Aluminum Anodised, Teach-In, With LED display, ultrasonic cone Lateral



MECHANICAL FEATURES

Ambient temperature	-25 °C ... 70 °C
Degree of protection (IP)	IP67
Design	Rod
Diameter detection	+
Furcate	-
Housing coating	Anodized
Housing material	Aluminum
Housing material, detail	Aluminum
Mounting distance	250 mm
Sensor height	84 mm
Sensor length	12 mm
Sensor width	12 mm

ELECTRICAL FEATURES

Absolute repeat accuracy	0.5 mm
Adjustable distance	40 mm ... 400 mm
Adjustable measuring range	+
Carrier frequency	300 kHz
Distance measuring sensors	+
Filling level measurement	-
IO-Link compatible	+
Load resistance (current output)	0.4 kOhm
Load resistance (voltage output)	10 kOhm
Measuring range length	100 mm ... 360 mm
Multiplex connection (switchover by means of IO-Link)	+
No-load current	35 mA
Number of pins	4
Operating voltage	18 V ... 30 V
Protection class	III
Rated switching current	150 mA
Readiness delay	300 ms
Reverse polarity protection	+
Sensing range	40 mm ... 400 mm

ELECTRICAL FEATURES

Setting procedure	Teach-In
Setting via teach-in	+
Short-circuit protection	+
Sound cone with small angle of beam spread	-
Sound outlet	Lateral
Switching frequency	10 Hz
Switching output (switchover by means of IO-Link)	+
Switching output with window function	-
Synchronization connection (switchover by means of IO-Link)	+
Synchronization input	-
Synchronization possible	-
Teach input (switchover by means of IO-Link)	+
Temperature drift	0.2 %
Type of analog output	0 V ... 10 V / 4 mA ... 20 mA
Type of electrical connection	Connector M8
Voltage type	DC
With LED display	+

OPTICAL FEATURES

Resolution	1 mm
High resolution	-

OTHER FEATURES

Dead zone	40 mm
Level detection	+
Loop control	-
Object detection on conveyor systems	+
Relative linearity deviation	0.8 %
With protective coating	-

Other


Packaging dimensions	150mm x 13.0mm x 160mm
Shipping weight	0.04kg
Tariff code	85365019

Classification

ipf product group	259
eClass 8.0	27272803
eClass 9.0	27272803
eClass 9.1	27272803
ETIM-5.0	EC001849
ETIM-6.0	EC001849
ETIM-7.0	EC001849

Connection

Dimensional drawing



Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Software

Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com

Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality.

LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.