

SS27012A

FLOW SENSORS • SENSORS FOR WATER

The function of the flow sensor is based on the calorimetric principle. The probe is heated up from the inside a few degrees Celsius in relation to the flow medium, in which it protrudes. When the medium flows, the heat generated in the probe is dissipated through the medium. The temperature within the sensor is measured and compared with the likewise measured medium temperature. From the obtained temperature difference the flow state of each medium can be derived. These sensors are applied in areas such as monitoring of cooling systems, ventilation systems, pump dry running by checking the presence of liquid or gas flows.



MECHANICAL DATA

Degree of protection (IP) of evaluation electronics	IP67
Degree of protection (IP) of measuring head	IP67
Flow rate	0.2 l/min
Flow rate	0 l/min
Housing design	Cuboid
Housing material	PBT
Medium temperature (MAX)	60 °C
Pressure resistance	10 bar
Sensing element material	Stainless steel 1.4571
Type of process connection	G1/4 inch

ELECTRICAL DATA

Adjustable responding value for flow for liquids (MAX)	0.2 m/s
Adjustable responding value for flow for liquids (MIN)	0.01 m/s
Max. output current	200 mA
Measuring principle of flow	Calorimetric
No-load current	50 mA
Operating voltage (MAX)	24 V
Operating voltage (MIN)	24 V
Readiness delay	20 ms
Response time	3000 ms
Type of electrical connection	Plug-in connection M12
Type of switching function	Normally open contact (NO)
Type of switching output	PNP
Voltage type	DC
With LED display	Yes

OTHER DATA

Cooling water circuits	Yes
Suitable for gases	No
Suitable for liquids	Yes

CONNECTION



Colors: 1 = BN (brown), 2 = WH (white), 3 = BU (blue), 4 = BK (black)

Functions: 1 = L+, 2 = n. c., 3 = L-, 4 = PNP NO

DIMENSIONAL DRAWING

INSTALLATION



Mounting / Installation may only be carried out by a qualified electrician!

DISPOSAL



SAFETY WARNINGS

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information!

Never use these devices in applications where the safety of a person depends on their functionality.